## **Active Polypropylene Fume Hood**



TopAir's Active Polypropylene Fume Hood is an advanced high quality system enhanced with innovative technology, offered at highly competitive prices.

The hood is made of high-quality non-corrosive polypropylene with excellent chemical resistance.

The Active Fume Hoods protect laboratory staff from noxious fumes released by acids, dangerous gas and organic solutions — materials and acids which regular steel hoods may not withstand. Harmful and unpleasant chemical fumes are removed from the controlled environment to facilitate a safe and pleasant work environment. The fume hood channels chemical vapors out of the building using an external fan installed on the roof or on an external wall.

The fume hood features a sensor which detects staff standing next to the unit, and accordingly, opens and closes the window automatically. The unit's fan speed changes according to the open/closed mode of the window, saving substantial energy.


- VAV system including 9" color touch screen
- Sensor detects staff presence and opens/closes the window, as well as adjusting fan speed to save energy
- Polypropylene structure with high chemical resistance
- One-piece welded structure
- Built-in polypropylene worktop
- Tempered glass sliding front sash
- Eco-friendly, cost-effective 800 LUX LED lighting separated from the work area
- Optional: sink/water tap/gas tap/vacuum tap/ electric sockets
- Includes polypropylene lower base Hood
- Optional: Variety of worktop materials
- EN-14175 / ASHRAE 110-1995 / CE certified

Upon a failure, the interior of the cabinet is lighted up in bright red, so that staff, including people with hearing issues, can easily detect the failure from a distance.

## **VAV System**

TopAir's reliable VAV (Variable Air Volume) system for fume hoods measures the air velocity using a high quality sensor. The data is converted to an analog signal that can control a VFD (Variable-Frequency Drive).

The system's key advantage is its ease of operation: an unskilled worker can easily calibrate, set the alarm and operation set points and control the system. The VAV system provides a safe energy-saving environment and can upgrade fume hoods to smart, advanced devices. TopAir's VAV system is provided as a complete installed product.



## **Models**

| Spec/Model  | FH-120-PP-ACT  | FH-150-PP-ACT           | FH-180-PP-ACT           | FH-200-PP-ACT           | FH-250-PP-ACT           |
|---|--|-------------------------|-------------------------|-------------------------|-------------------------|
| External<br>Dimensions  | 1200 x 830 x 2320<br>mm  | 1500 x 830 x 2320<br>mm | 1800 x 830 x 2320<br>mm | 2000 x 830 x 2320<br>mm | 2000 x 830 x 2320<br>mm |
| WxDxH   | 47.3x 32.6 x 91.3"   | 59.0 x 32.6 x 91.3"     | 70.9 x 32.6 x 91.3"     | 78.7 x 32.6 x 91.3"     | 98.4 x 32.6 x 91.3"     |
| WE CAN CUSTOMIZE TO ANY SIZE - EVEN A SINGLE UNIT! CONTACT US FOR DETAILS |  |                         |                         |                         |                         |
| Workspace   | 1000 x 630 x 1170<br>mm  | 1300 x 630 x 1170<br>mm | 1600 x 630 x 1170<br>mm | 1800 x 630 x 1170<br>mm | 2300 x 630 x 1170<br>mm |
| (W x D x H)   | 39.4 x 24.8 x 46"  | 51.2 x 24.8 x 46"       | 63 x 24.8 x 46"         | 70.8 x 24.8 x 46"       | 90.5 x 24.8 x 46"       |
| Front Sash<br>Max Opening   | 720 mm / 28.3"   | 720 mm / 28.3"          | 720 mm / 28.3"          | 720 mm / 28.3"          | 720 mm / 28.3"          |
| Production /<br>test Standard   | EN-14175 / ASHRAE 110-1995   |                         |                         |                         |                         |
| Air Velocity  | 0.5±0.1 m/s, 100±20 FPM  |                         |                         |                         |                         |
| Hood<br>Material  | White Polypropylene  |                         |                         |                         |                         |
| Work Table<br>Material  | HPL/ Ceramic / Epoxy / PP / Stainless steel  |                         |                         |                         |                         |
| Control System  | VAV System with 9" color touch screen  |                         |                         |                         |                         |
| Optional  | Water tap/ gas tap / vacuum tap/ pp sink   |                         |                         |                         |                         |
| Power Supply  | 110 / 220V, 50/60 Hz. Includes a single phase power supply. A three-phase power supply can be specially ordered. |                         |                         |                         |                         |
| Illumination  | 800 LUX LED lights   |                         |                         |                         |                         |

## **Accessories**

| Description   | Model           |
|---|-----------------|
| Kit for Fume Hood includes: 1 water tap, 1 gas tap, 1 cup sink and 4 power outlets              | FH-KIT          |
| Gas tap   | FH-GTAP         |
| Water tap   | FH-WTAP         |
| Polypropylene cup sink  | FH-PP-SINK      |
| Polypropylene sink 30 x 40  | FH-SINK-3040    |
| Power outlet  | FH-SOCKET       |
| Air flow monitor with audible alarm VAV+VFD installed, including 9" LCD touch screen controller | FH-VAV          |
| Centrifugal fan 0.75 kw 2800 RPM/IE3  | FH-FAN-750      |
| Centrifugal fan 1.1 KW 2800 RPM/IE3 DIA 300 mm  | FH-FAN-1100-300 |

Tel: 1-855-6-TOPAIR International: +1-855-686-7247 Email: sales@topairsystems.com www.topairsystems.com | Headquarters: 300 First Avenue, Suite 102, Needham, MA 02494 USA